

Serial No. 10/064,322
Filed: July 2, 2002
Page 2 of 10

Examiner: Theresa T. Snider
Group Art Unit: 1744

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application.

Listing of Claims:

1. (Cancelled)
2. (Currently Amended) The extraction surface cleaning apparatus according to claim 1+23 wherein the sinusoidally arranged bristle brush has at least four rows of bristles.
3. (Currently Amended) The extraction surface cleaning apparatus according to claim 1+23 wherein the helically arranged twist wire brush comprises a continuous helical array of radially extending bristles bound by a pair of twisted wires forming a spindle.
4. (Cancelled)
5. (Cancelled)
6. (Previously Presented) The extraction surface cleaning apparatus according to claim 20 wherein the resiliently mounted projection is mounted on an integrally formed flexible tab on the at least one arm.
7. (Cancelled)
8. (Previously Presented) The extraction surface cleaning apparatus according to claim 21 wherein the elongated cover is a fabric and is secured onto the elongated agitation brush with a hook and pile fastener.
9. (Currently Amended) The extraction surface cleaner apparatus according to claim 1+23 wherein the housing is a hand held deep cleaner housing.
10. (Currently Amended) The extraction surface cleaning apparatus according to claim 1+23 wherein the housing comprises a base including a pair of wheels for movement along the surface to be cleaned, and further includes a handle pivotally mounted to the base for manipulation of the base along the surface to be cleaned.
11. (Currently Amended) The extraction surface cleaning apparatus according to claim 1+23 wherein the working air conduit includes a flexible hose which is joined at one end to the housing and further comprising a hand tool mounted to a free end of the hose and the suction nozzle and the elongated agitation brush are mounted in the hand tool.

Serial No. 10/064,322
Filed: July 2, 2002
Page 3 of 10

Examiner: Theresa T. Snider
Group Art Unit: 1744

12. (Previously Presented) The extraction surface cleaning apparatus according to claim 11 wherein the drive motor is a turbine motor mounted in the hand tool.
13. (Previously Presented) An extraction surface cleaning apparatus having;
a housing with a fluid dispensing system and a fluid recovery system mounted thereto;
the fluid dispensing system including:
a fluid dispenser for applying fluid to a surface to be cleaned;
a fluid supply chamber for holding a supply of cleaning fluid;
a fluid supply conduit fluidly connected to the fluid supply chamber and to the fluid dispenser for supplying fluid to the dispenser;
the fluid recovery system including:
a recovery chamber for holding recovered fluid;
a suction nozzle;
a working air conduit extending between the recovery chamber and the suction nozzle; and
a vacuum source in fluid communication with the recovery chamber for generating a flow of working air from the suction nozzle through the working air conduit and to the recovery chamber to thereby draw dirty fluid from the surface to be cleaned through the suction nozzle and the working air conduit, and into the recovery chamber;
an elongated agitation brush mounted to the housing adjacent to the suction nozzle for rotation about a longitudinal axis; and
a drive motor mounted in the housing and connected to the agitation brush for rotation of the elongated agitation brush about the longitudinal axis;
the improvement which comprises:
the elongated agitation brush is mounted to the housing through a pair of arms which are pivotally attached at one end to the housing and rotatably support the elongated agitation brush at another end thereof; and
a spring between the arms and the housing biases the elongated agitation brush with respect to the housing into contact with the surface to be cleaned.
14. (Cancelled)

Serial No. 10/064,322
Filed: July 2, 2002
Page 4 of 10

Examiner: Theresa T. Snider
Group Art Unit: 1744

15. (Previously Presented) The extraction surface cleaning apparatus according to claim 22 wherein the resiliently mounted projection is mounted on an integrally formed flexible tab on the at least one arm.

16. (Previously Presented) An extraction surface cleaning apparatus having;
a housing with a fluid dispensing system and a fluid recovery system mounted thereto;
the fluid dispensing system including:
a fluid dispenser for applying fluid to a surface to be cleaned;
a fluid supply chamber for holding a supply of cleaning fluid;
a fluid supply conduit fluidly connected to the fluid supply chamber and to the fluid dispenser for supplying fluid to the dispenser;
the fluid recovery system including:
a recovery chamber for holding recovered fluid;
a suction nozzle;
a working air conduit extending between the recovery chamber and the suction nozzle; and
a vacuum source in fluid communication with the recovery chamber for generating a flow of working air from the suction nozzle through the working air conduit and to the recovery chamber to thereby draw dirty fluid from the surface to be cleaned through the suction nozzle and the working air conduit, and into the recovery chamber;
an elongated agitation brush mounted to the housing adjacent to the suction nozzle for rotation about a longitudinal axis; and
a drive motor mounted in the housing and connected to the agitation brush for rotation of the elongated agitation brush about the longitudinal axis;
the improvement which comprises:
a fabric cover encircling the elongated agitation brush and removably mounted thereto for contacting the surface to be cleaned.
17. (Previously Presented) The extraction surface cleaning apparatus according to claim 16 wherein the elongated cover is a fabric and is secured onto the elongated agitation brush with a hook and pile fastener.

Serial No. 10/064,322
Filed: July 2, 2002
Page 5 of 10

Examiner: Theresa T. Snider
Group Art Unit: 1744

18. (Previously Presented) An extraction surface cleaning apparatus having;
a housing with a fluid dispensing system and a fluid recovery system mounted thereto;
the fluid dispensing system including:
 a fluid dispenser for applying fluid to a surface to be cleaned;
 a fluid supply chamber for holding a supply of cleaning fluid;
 a fluid supply conduit fluidly connected to the fluid supply chamber and to the
fluid dispenser for supplying fluid to the dispenser;
the fluid recovery system including:
 a recovery chamber for holding recovered fluid;
 a suction nozzle;
 a working air conduit extending between the recovery chamber and the suction
nozzle; and
 a vacuum source in fluid communication with the recovery chamber for
generating a flow of working air from the suction nozzle through the working air conduit and to
the recovery chamber to thereby draw dirty fluid from the surface to be cleaned through the
suction nozzle and the working air conduit, and into the recovery chamber;
 an elongated agitation brush mounted to the housing adjacent to the suction nozzle for
rotation about a longitudinal axis and adapted to agitate the surface to be cleaned; and
 a drive motor mounted in the housing and connected to the agitation brush for rotation of
the elongated agitation brush about the longitudinal axis;
the improvement which comprises:
 the elongated agitation brush is mounted to the housing through a pair of arms
which are pivotally attached at one end to the housing and rotatably support the elongated
agitation brush at another end thereof; and
 at least one of the arms has a resiliently mounted projection which bears against a
surface of the housing to resist transient vibrations of the elongated agitation brush with respect
to the housing.
19. (Previously Presented) The extraction surface cleaning apparatus according to claim 18
wherein the resiliently mounted projection is mounted on an integrally formed flexible tab on the

Serial No. 10/064,322
Filed: July 2, 2002
Page 6 of 10

Examiner: Theresa T. Snider
Group Art Unit: 1744

at least one arm.

20. (Previously Presented) An extraction surface cleaning apparatus having;
- a housing with a fluid dispensing system and a fluid recovery system mounted thereto;
 - the fluid dispensing system including:
 - a fluid dispenser for applying fluid to the surface to be cleaned;
 - a fluid supply chamber for holding a supply of cleaning fluid;
 - a fluid supply conduit fluidly connected to the fluid supply chamber and to the fluid dispenser for supplying fluid to the dispenser;
 - the fluid recovery system including:
 - a recovery chamber for holding recovered fluid;
 - a suction nozzle;
 - a working air conduit extending between the recovery chamber and the suction nozzle; and
 - a vacuum source in fluid communication with the recovery chamber for generating a flow of working air from the suction nozzle through the working air conduit and to the recovery chamber to thereby draw dirty fluid from the surface to be cleaned through the suction nozzle and the working air conduit, and into the recovery chamber;
 - an elongated agitation brush mounted to the housing adjacent to the suction nozzle for rotation about a longitudinal axis and adapted to agitate the surface to be cleaned; and
 - a drive motor mounted in the housing and connected to the agitation brush for rotation of the elongated agitation brush about the longitudinal axis;
- the improvement which comprises:
- the elongated agitation brush is selected from a multi-row, sinusoidally arranged bristle brush and a helically arranged twisted wire brush;
 - the elongated agitation brush is mounted to the housing through a pair of arms which are pivotally attached at one end to the housing and rotatably support the elongated agitation brush at another end thereof;
 - a spring between the arms and the housing biases the elongated agitation brush with respect to the housing into contact with the surface to be cleaned; and

Serial No. 10/064,322
Filed: July 2, 2002
Page 7 of 10

Examiner: Theresa T. Snider
Group Art Unit: 1744

at least one of the arms has a resiliently mounted projection which bears against a surface of the housing to resist transient vibrations of the elongated agitation brush with respect to the housing.

21. (Previously Presented) An extraction surface cleaning apparatus having;
a housing with a fluid dispensing system and a fluid recovery system mounted thereto;
the fluid dispensing system including:

a fluid dispenser for applying fluid to the surface to be cleaned;

a fluid supply chamber for holding a supply of cleaning fluid;

a fluid supply conduit fluidly connected to the fluid supply chamber and to the fluid dispenser for supplying fluid to the dispenser;

the fluid recovery system including:

a recovery chamber for holding recovered fluid;

a suction nozzle;

a working air conduit extending between the recovery chamber and the suction nozzle; and

a vacuum source in fluid communication with the recovery chamber for generating a flow of working air from the suction nozzle through the working air conduit and to the recovery chamber to thereby draw dirty fluid from the surface to be cleaned through the suction nozzle and the working air conduit, and into the recovery chamber;

an elongated agitation brush mounted to the housing adjacent to the suction nozzle for rotation about a longitudinal axis and adapted to agitate the surface to be cleaned; and

a drive motor mounted in the housing and connected to the agitation brush for rotation of the elongated agitation brush about the longitudinal axis;

the improvement which comprises:

the elongated agitation brush is selected from a multi-row, sinusoidally arranged bristle brush and a helically arranged twisted wire brush; and

further comprising a fabric cover encircling the elongated agitation brush and removably mounted thereto for contacting the surface to be cleaned.

22. (Previously Presented) An extraction surface cleaning apparatus having;

Serial No. 10/064,322
Filed: July 2, 2002
Page 8 of 10

Examiner: Theresa T. Snider
Group Art Unit: 1744

a housing with a fluid dispensing system and a fluid recovery system mounted thereto;
the fluid dispensing system including:

- a fluid dispenser for applying fluid to a surface to be cleaned;
- a fluid supply chamber for holding a supply of cleaning fluid;
- a fluid supply conduit fluidly connected to the fluid supply chamber and to the

fluid dispenser for supplying fluid to the dispenser;

the fluid recovery system including:

- a recovery chamber for holding recovered fluid;
- a suction nozzle;
- a working air conduit extending between the recovery chamber and the suction

nozzle; and

a vacuum source in fluid communication with the recovery chamber for generating a flow of working air from the suction nozzle through the working air conduit and to the recovery chamber to thereby draw dirty fluid from the surface to be cleaned through the suction nozzle and the working air conduit, and into the recovery chamber;

an elongated agitation brush mounted to the housing adjacent to the suction nozzle for rotation about a longitudinal axis; and

a drive motor mounted in the housing and connected to the agitation brush for rotation of the elongated agitation brush about the longitudinal axis;

the improvement which comprises:

the elongated agitation brush is mounted to the housing through a pair of arms which are pivotally attached at one end to the housing and rotatably support the elongated agitation brush at another end thereof;

a spring between the arms and the housing biases the elongated agitation brush with respect to the housing into contact with the surface to be cleaned; and

at least one of the arms has a resiliently mounted projection which bears against a surface of the housing to resist transient vibrations of the elongated agitation brush with respect to the housing.

23. (New) The extraction surface cleaning apparatus according to claim 13 wherein the

Serial No. 10/064,322
Filed: July 2, 2002
Page 9 of 10

Examiner: Theresa T. Snider
Group Art Unit: 1744

elongated agitation brush is selected from a multi-row, sinusoidally arranged bristle brush and a helically arranged twisted wire brush.